



Belt : 3NVT

Construction



Top Cover

Material : NBR
Color : Brown
Profile : VT
Thickness : 0,185
Hardness - ShA : 70



Bottom Cover

Material : Polyester
Color : Brown
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 3
Fabric Material : Polyester
Lateral Rigidity (Weft) : Flexible
Internal Material : NEO

Working Characteristics

Overall Thickness : 0,269
Working Load - lbs/in : 135


Overall Weight - lbs/ft² : 1,21
% Of Elongation : 1

Working Temperature (°F) : -20 / 250

Coefficient of friction - Bottom

-On Steel 0,4
-On Plastic 0,3
-On Rollers 0,05

Minimum Diameter (F) 2"
Minimum Diameter (C) 2"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 15
Clipper® Lacing 2
Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA No Antistatic No Antimicrobial No