

Belt : *FELB-2.5-ACR ITO50*

Construction



Top Cover

Material :	PU
Color :	Blue
Profile :	MRT
Thickness :	-
Hardness - ShA :	80

Bottom Cover

Material :	PU
Color :	Blue
Profile :	Text.
Thickness :	-
Hardness - ShA :	80

Plies / Weaving

Number of plies :	1
Fabric Material :	Kevlar
Lateral Rigidity (Weft) :	Flexible
Internal Material :	-


Working Characteristics

Overall Thickness :	0,098	Overall Weight - lbs/ft ² :	-	Working Temperature (°F) :	-40 / 120
Working Load - lbs/in :	11,6	% Of Elongation :	-		

Coefficient of friction - Bottom

-On Steel	0,45
-On Plastic	-
-On Rollers	0,05

Minimum Diameter (F)	0,5625"
Minimum Diameter (C)	0,5625"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing	7	Bolt Hinged Fasteners	N/R
Clipper® Lacing	1XSP	Rivet Hinged Fasteners	N/R
Ready Set™ Fasteners	62		

Recommended Joint : Endless

Hot Splice	EZ	Cold Splice	N/R
Cooking Temperature (°F)	On Demand	Glue To Use	N/R
Pressure (lbs)	On Demand		

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----