


Belt : FMW-3

Construction



Top Cover

Material : PU
Color : Beige
Profile : Smooth
Thickness : -
Hardness - ShA : 96



Bottom Cover

Material : PU
Color : Beige
Profile : Smooth
Thickness : -
Hardness - ShA : 95

Plies / Weaving

Number of plies : 0
Fabric Material : -
Lateral Rigidity (Weft) : Flexible
Internal Material : PU

Working Characteristics

Overall Thickness : 0,118
Working Load - lbs/in : 67


Overall Weight - lbs/ft² : 0,78
% Of Elongation : -

Working Temperature (°F) : -20 / 140

Coefficient of friction - Bottom

-On Steel 0,36
-On Plastic -
-On Rollers 0,05

Minimum Diameter (F) 1,625"
Minimum Diameter (C) 1,625"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 15
Clipper® Lacing 1
Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EB
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice N/R
Glue To Use N/R

Other Specifications

FDA Yes Antistatic No Antimicrobial No