


Belt : L500

Construction



Top Cover

Material : XNBR
Color : Blue
Profile : Text.
Thickness : -
Hardness - ShA : -



Bottom Cover

Material : XNBR
Color : Blue
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 2
Fabric Material : Polyester
Lateral Rigidity (Weft) : Rigid
Internal Material : PA

Working Characteristics

Overall Thickness : 0,06
Working Load - lbs/in : 42


Overall Weight - lbs/ft² : 0,37
% Of Elongation : 2

Working Temperature (°F) : -4 / 176

Coefficient of friction - Bottom

-On Steel 0,5
-On Plastic 0,5
-On Rollers 0,05

Minimum Diameter (F) 1,97"
Minimum Diameter (C) 1,97"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 7
Clipper® Lacing 1XSP
Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice N/R
Glue To Use N/R

Other Specifications

FDA No Antistatic Yes Antimicrobial No